

PrOffice

The Affordable Power Solution for Home and Office Environment

- **Microprocessor Controlled**
Guarantees high reliability
- **Internet Ready**
Protection for Modem/Phone line
- **Built in Smart RS232 and USB port**
- **Intelligent Battery Management**
- **User-Replaceable Battery Design**
- **Both Battery and surge protected outlets**
- **Audible Warning - Abnormal Conditions**
- **Compact Design**
- **Comprehensive Warranties**
Three year replacement warranty on the UPS and two year replacement warranty on the battery

PrOffice is a Stand By UPS with 5 Australian three pin socket outlets. Three of these are battery supported, uninterruptible power outlets whilst the remaining two are surge protected. This allows for critical equipment like computers, monitors and modems to be protected from power outages as well as power spikes and surges. Simultaneously, less critical peripherals including printers and scanners may be surge protected with the same unit by plugging directly into the two surge protected outlets.

There is also provision to surge protect devices connected to the telephone service, such as phone, fax and modem.

The UPS can be operated in a vertical or horizontal position and there are also facilities for wall mounting (ideal for PABX).

Upsonic Power offers full workshop facilities in all major centres, however, if desired, the battery can be replaced by the user.

Shutdown software may be downloaded from the Internet at <http://www.ups-software-download.com/>

The Perfect Solution...



...For Home and Office

**POWER FOR THE
NON-STOP WORLD**

www.upsonic.com.au
Phone 1800 634 307



Specifications

Model	PrOffice	PrOffice 650
Capacity	VA / W	650VA / 390W
Input	Voltage	230VAC
	Phase	Single Phase
Output (Inverter Mode)	Voltage Range	230 VAC +/- 10%
	Frequency	50Hz +/- 1Hz
	Waveform	Modified Sine Wave
Transfer Time	Typical	2 - 6 mSec.
Battery	Type	12V/7AH x 1 Lead Acid, maintenance free
	Recharge Time	10 Hrs up to 90%
	Backup Time	10 minutes (at a PC load with 17" monitor)
Display	LED	Power on, Backup Mode
Audible Alarm	Battery Mode	Sounding every 10 seconds
Indicators	Low Battery	Sounding every second
	Battery Replacement	Sounding every 2 seconds
	Fault	Continuously Sounding
Protection	Full Protection	Deep Discharge, Overcharge, Short Circuit Protection
		RJ 11 Modem/Telephone Protection x 3, EMC EN 50091-1-, 1996, EN 60950:1992+A1:1993, +A2:1993, AS/NZS 60950:2000, EMI C -Tick (240V, 50 Hz), AS-NZS3548
		Safety CE, A -Tick
Mechanical	Dimension (WxHxD mm)	192 x 90 x 297
	Weight (W Battery Kg)	6.2 kgs
Environment	Operation Temperature	0-40° C
	Operation Humidity	20-90% Non-condensing
Interface	Smart RS 232	Windows 95/98/NT/2000/ME/XP, Novell and Linux
	USB Port	Standard

*3 Operational Positions

Flat
Wall Mount
Vertical



*Modem/Phone Line Surge Protection

PrOffice is equipped with 1 in 2 out RJ-11 surge protector to protect against spikes and surges through telephone/network line at the same time.

*USB Interface

Plug and Play

*On/Off Switch

*RS-232 Interface

Monitoring UPS status through RS-232 communication port by downloaded software

Upsonic Power Pty Ltd

ABN 51 070 890 390
National Sales 1800 634 307
National Fax 1800 634 308

Melbourne
9 Nicole Way
Dandenong South, Vic 3175

Telephone: (03) 9706 0045
Facsimile: (03) 9706 8003

www.upsonic.com.au
Phone 1800 634 307



**POWER FOR THE
NON-STOP WORLD**